

Frequently Asked Questions

What exactly is a Smoke Test?

A crew from DPC Engineering, LLC (DPC) will use a high-capacity blower technique to test each sewer line with smoke. Smoke blowers are placed on manholes and smoke is blown through the sewer system. Any location where smoke is identified during the test, except plumbing vent stacks, is a potential infiltration/inflow source for storm water to enter the sewer system. These locations will be documented via pictures and sketches.

What is the benefit to the County for performing a Smoke Test?

Smoke testing is one technique utilized to identify sections of sewers that may exhibit inflow during heavy rainfall. Smoke testing is best used to detect inflow sources such as roof downspouts, driveway, yard and area drains, foundation drains, faulty connections, and storm water drainage system cross connections. It can also detect structural damages and leaking joints in sewer pipes.

How will residents know when Smoke Testing will be performed in their neighborhoods?

Prior to beginning the smoke testing, DPC will give notices to all homes/buildings on the streets to be smoke tested at least 48 to 72 hours in advance.

How are County crews recognizable in the field?

DPC personnel are uniformed with high-visibility vests carrying DPC logo. Crew members operate from vehicles with proper signage for ease of recognition.

Is the smoke that is used hazardous?

The smoke that comes out of the vent stacks on houses or holes in the ground is non-toxic, harmless. It does not create a fire hazard. Police and Fire Departments will be made aware of the test areas and schedule.

Do residents have to do anything to prepare their homes for Smoke Testing?

Plumbing drain traps need to be filled with water to prevent the smoke from entering the building. Run the faucet for 30-60 seconds or pour about 3 cups of water in floor and sink drains, filling the traps. Make sure to check seldom used floor drains and plumbing fixtures in your home. If smoke does enter, the resident should consult a licensed plumber. If smoke from the testing can enter through faulty plumbing, the potential exists for dangerous sewer gases to also enter the home.

Does the resident need to be home when the Smoke Testing is performed?

Homeowners do not need to be home and at no time will field crews need to enter the residence. Field inspectors will be documenting the testing, taking photos and measuring distances so that the defects may be found at a later date and repaired.

What happens after the smoke testing has been completed?

Residents who need to make corrections will be notified explaining the nature of defect found, ways to correct it, and a need for licensed sewer contractor to make

corrections, if need be. Again, most corrections can be easy fixes, such as disconnecting a downspout from the ground and letting the water flow above ground away from the home.